





PRODUCT NUMBER	PITCH
OQxx12x000J0G	3.50mm



RECOMMENDED P.C.B LAYOUT
TOP VIEW



Material:

- Item ③ Male contact pin: Copper Tin plated
- Item ④ Terminal housing: Thermoplastic (UL94V-0)

Electrical:

- Voltage rating: 300V/300V
- Current rating: 10A/10.5A
- Withstanding Voltage: 1.6 KV/2.5KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 260°C±5°C/5 Sec
- Safety Approval:

cULus /VDE

DIMENSION

Dim A	(N-1)×3.5+4.90
Dim B&C	(N-1)×3.5

N= NUMBER OF POLES

Poles	Tolerance
2P-6P	±0.15
7P-12P	±0.20
13P-18P	±0.25
19P-24P	±0.30

PART NO.: OQ xx 1 2 x 0 00J0 G

- | | | |
|--------------|---------------------|--------------------------|
| No. of poles | 0 Black (RAL9005) | RoHS compliant (lead<4%) |
| 02 2 poles | 2 Red (RAL3001/D) | In copper Alloy |
| 03 3 poles | 3 Orange(RAL2011/P) | |
| | 4 Yellow(RAL1018/A) | |
| 24 24 poles | 5 Green(RAL6018/T) | |
| | 6 Blue (RAL5015/A) | |
| | 8 Grey(RAL7035/D) | |
| | 9 White(RAL1102) | |
| | C Green(RAL6018/U) | |

mat'l. code		surface ASME Y14.5	tolerance ASME Y14.5	projection 	product family TERMINAL BLOCK
ltr	ecn no	dr	date	tolerances unless otherwise specified	title TERMINAL BLOCK PLUGGABLE SOCKET,VERTICAL
				angles X±0.5 X.X±0.3 X°±1° X.XX±0.1	
				scale MM	dwg no OQxx12x000J0G sheet 1 of 1 size A4
				dr HANKE FENG 032614 enrg HANKE FENG 032614 chr SHI JUN 032614 appd SHI JUN 032614	
sheet index	revision sheet	A	1		type CUSTOMER Drawing