



Notes:

1. Electrical Specifications:
 - Meets EIA/TIA-568-B.2 Cat.5e Specification
 - Contact Resistance: 20mOhm max.
 - Insulation Resistance: 500MOhm min. @ 100 VDC
 - Current Rating: 1.2A max. at 25° C
 - Working Voltage: 100 VDC
 - DWV: 1000 VDC/60s Contact to Contact, 1500 VDC/60s Contact to Metal Shell
 - Operating Temperature: -40° C to +85° C

2. Material and Finish:

- a) - Receptacle Housing, Zinc Die-Cast, Nickel Plated
- Metal HEX Cover, Panel Nut: Brass, Nickel Plated
- Ball Chain: Copper Alloy, Nickel Plated
- Panel Gasket: Silicon, Color: White
- b) - Cover Gasket: Silicon, Color: White
- RJ45 Jack Metal Shell: Copper Alloy, Nickel Plated
- RJ45 Jack Plastic Housing: Glass filled PBT UL94 V-0, Color: Black
- RJ45 Jack Contacts: Phosphor Bronze, Finish: 50u" Gold min. over Nickel

3. Connector can be front or rear mounted to a maximum panel thickness of 3.2mm.
4. IP67 rated when fully mated with appropriate mating connector

Directive 2002/95/EC RoHS Compliant

Description	Part Number
Metal Version Receptacle + HEX 32 Cover with Shielded RJ45 Inline Coupler	17-101884
Metal Version Receptacle + HEX 32 Cover with Unshielded RJ45 Inline Coupler	17-101894

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION. DO NOT ALTER CAD DRAWING BY HAND	Customer:			Tolerance Unless otherwise specified 0 PLC ±0.50 1 PLC ±0.38 2 PLC ±0.25 3 PLC ±0.10 ANGLES ±3°		Scale: 1:2:1	Dim. in mm
	Name	Title	Approval Date			Material: See Notes	
						Title: Receptacle + HEX 32 Cover Assembly Kit with Cat. 5e RJ45 Inline Coupler (Metal Version)	
	d	1	Jan/12/2012			Vincent Ke	Norm
c	2	Mar/08/2011	Vincent ke	D-old			
b	1	Sep/28/2010	Vincent Ke				
a	original						
Rev.	Changes	Date	Name			Drawing No.: 17K1A162	DIN A3
Part No.: SEE P/N TABLE						Sheet 1/1	