



- NOTES:**
- MATERIALS:**  
 HOOD, GLAND, COMPR.-RING: ABS UL94 V-0 METALLIZED  
 FRONTSEALING: SILICONE VMQ BLUE  
 CABLE SEALING: NBR BLACK  
 JACK-SCREW: STAINLESS STEEL  
 O-RING: NBR BLACK  
 CABLE STRAIN RELIEF: STEEL, NI-PLATED  
 SCREWS: STEEL, NI-PLATED  
 SHIELDING BRACKET: CU-ALLOY, NI-PLATED
  - TEMPERATURE RANGE: -30°C TO +80°C
  - RECOMMENDED TORQUE FOR SCREW:  
 35Ncm (3.1 in.LB)  
 MAX. TORQUE: 68Ncm (6 in.LB)
  - SINGLE PACKED

\* COMPLETELY TIGHTENED

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONECC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		dim. in mm		scale: 1,5:1 (1:1)		
					material: SEE NOTES		
			date		title:		
			name		WATER RESISTANT D-SUB HOOD		
		drawn 07.02.2014		SHIELDED 50 POS.			
		appd. 07.02.2014		JACKSCREW 4-40UNC STAINLESS STEEL			
		norm		dwg no:			
		d-old		15K1A1154			
1 x b		Ä 5092		12.03.14		DIN-A3	
a		Origin				sh: 1	
rev. description		date		name		part no: 15-004800	

