



NOTE: ALL LEADS 8" OUT MIN.

ELECTRICAL DATA:	
Turns ratio:	1 (WHT-BLK) : 7.303 (RED - RED)
Exciting Current	@ 240V, 50Hz, BLK - WHT = 450 mA Max.
DCR	@ 20C, BLK - WHT = 0.348 Ω ±20%
	@ 20C, BRN - BLU = 0.381 Ω ±20%
	@ 20C, RED - RED = 12.42 Ω ±20%
	@ 20C, VIO - VIO = 0.921 Ω ±20%
	@ 20C, GRN - GRN = 0.008 Ω ±20%
Pri. Voltage	100, 110, 120, 200, 220, 240V 50/60 Hz
Sec. Voltage (RMS)	850VCT (Inner tap 800 VCT) @ 1.0A / 60 V @ 0.20A / 6.3V @ 12 A
No Load Voltage	876.2 VCT (825.0 VCT) / 61.0 V / 6.428 VCT
Weight	29.2 LBS

DIMENSIONS:	
A	5.35" ±0.063
B	6.40" ±0.125
C	6.40" ±0.063
D	3.500" ±0.063
E	4.50" ±0.063
G	0.203" x 0.630" ±0.015

REV.#	REVISION	DATE	HAMMOND MANUFACTURING™		ELECTRONIC DIVISION	
0	RELEASED.	11/11/11			52 RANKIN PLACE, WATERLOO, ONTARIO, N2J 3Z5	
			DWG. BY: D.Hutt	CHK'D BY:	TITLE: POWER TRANSFORMER	PH # (519) 886-6181 FAX # (519) 886-9540
			DATE: 10/11/11	APP'D. BY:	DWG. NO. 379WX	
				DIMENSIONS: IN(X) MM()		